

## High-Performance LCD Expansion Module

The Yealink EXP20 is the next iteration of the company's flexible and powerful SIP-T27G, SIP-T27P and SIP-T29G advanced IP phone models.

The EXP20 contains a large and user-friendly liquid crystal display (LCD) interface that measures 160x320 pixels, as well as contains 20 physical, dual-color LED keys. The additional screen space and added number of buttons simplifies user navigation and streamlines essential operational functions such as speed dial, BLF, BLA, call forwarding, transfer and hold. Up to six EXP20 phone systems can be strung together on a single daisy chain.

The advanced new Yealink EXP20 is an ideal IP phone system for receptionists, administrative assistants or contact center workers who need to monitor and manage a large volume of calls on a regular basis.



### Key Features and Benefits

#### An All New Design

The EXP20 touts an all-new design that mirrors the eloquent look and feel of the T27G, T27P and T29G models. The solution brings to the table multiple convenient, user-friendly features such as rubber feet covers in order to prevent sliding, as well as a flexible base that allows the phone to stand in multiple dynamic positions. These features, among many others, contribute to a more enjoyable user experience.

#### A Richer Visual Experience

The solution's expansive screen, combined with an added backlight and multi-page layout, simplifies navigability for the end user. These functionalities, combined with 38 programmable LED keys, provides the rich visual experience that professionals need to exceed in today's demanding workplace.

#### Expandability

The EXP20 supports up to six expansion modules. It should be noted, however, that if you exceed two connections, the device will require a conventional power supply of 5V/1.2A.

- > A diverse range of actionable, LCD-accessible icons
- > 160x320 graphic LCD with backlight
- > 20 physical, dual-color LED programmable keys
- > 18 additional keys available
- > Supports up to six modules
- > Two accessible pages
- > Stand with two adjustable angles
- > Two or less expansion modules can be powered by the host phone

### Display

- > 160x320 graphic LCD
- > LCD Backlight
- > Two accessible pages
- > A diverse range of actionable, LCD-accessible icons

### Features Keys and Indicator

- > 20 physical, dual-color LED programmable keys
- > 18 additional keys available
- > Programmable keys enable users to partake in advanced call functions such as: BLF list, multi-person conferencing, call forwarding, LDAP, XML browser functionality

### Physical Feature

- > Stand with two adjustable angles
- > Two or less expansion modules can be powered by the host phone
- > Supports up to six modules
- > 2xRJ12 (6P6C) ports for data in and out
- > Max power consumption (PSU): 0.67W
- > Dimension (W\*D\*H\*T):  
122mm\*143mm\*110mm\*45mm
- > Applies to Yealink SIP-T27G/SIP-T27P/ SIP-T29G
- > Operating temperature: -10~50°C (+14~122 °F)
- > Operating humidity: 10%-95%



SIP-T27P+EXP20



SIP-T29G+EXP20



### **About Yealink**

Yealink is a global leading provider of enterprise communication and collaboration solutions, offering video conferencing service to worldwide enterprises. Focusing on research and development, Yealink also insists on innovation and creation. With the outstanding technical patents of cloud computing, audio, video and image processing technology, Yealink has built up a panoramic collaboration solution of audio and video conferencing by merging its cloud services with a series of endpoints products. As one of the best providers in more than 140 countries and regions including the US, the UK and Australia, Yealink ranks No.1 in the global market share of SIP phone shipments.

### **Copyright**

Copyright © 2017 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

Copyright © 2017 Yealink(Xiamen) Network Technology CO., LTD. All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.