# Yealink

# SIP-T42U

# A Well-Rounded SIP Phone for Clear Communications

The SIP-T42U IP phone is a feature-rich business tool for excellent communications and extended functionality. Coming with plentiful built-in programmable keys, this 12-line IP phone guarantees the enhanced productivity. United Yealink Optima HD Voice technology and wideband codec of Opus, the T42U awards you the superb audio quality and crystal-clear voice communications. The phone feels quicker and more responsive when performing call features. Moreover, the T42U puts dual USB ports in a phone that makes Bluetooth, Wi-Fi, USB headset and USB recording come true, and you can use any two of them freely according to your needs. The Yealink new T4U series offers the same elegant appearance as the T4 line, but with improvements for greater interoperability and better collaboration.











Gigabit



#### Optima HD Voice

Ports

Acoustic Shield

Unified **Opus** Codec Firmware

## **Key Features and Benefits**

Dual USB

## Easy Customization and High Expansibility

Accompanied by two USB ports, the T42U is your right-hand man in the office that makes Bluetooth, Wi-Fi, USB headset and USB recording possible, and you can use any two of them freely according to your needs to enrich phone features. Meanwhile, the phone has three pages of flexible buttons that can be easily programmed with 15 paperless DSS keys at most.

## HD Audio

Yealink Optima HD Voice technology combines cutting-edge hardware and software with wideband technology for maximum acoustic performance. Being a totally open, highly versatile audio codec, Opus, is designed to perform a higher HD audio quality than other wideband codecs in a high network bandwidth; However, if your current network quality is poor, Opus can provide you with a better audio quality than other narrowband codecs. And its hearing aid compatible (HAC) handset helps the person who is with hearing loss to hear the voice more clearly.

## Efficient Installation and Provisioning

Yealink T4U series supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings, which makes the T4U series simple to deploy, easy to maintain and upgrade. Furthermore, a unified firmware and auto-p template that applies to all T4U phone models, saves even more time and costs for businesses, as well as simplifies the management and maintenance.

## Secure Transport and Interoperability

Yealink T4U series uses SIP over Transport Layer Security (TLS/SSL), which is the latest network security technology. It's also compatible with leading soft switch suppliers, such as 3CX, Broadsoft Broadworks. Moreover, it is carried with dual fimrware images that gives you a enterprise-level protection to avoid bricking your system once upgrade failed.

- 2.7" 192x64-pixel graphical LCD with backlight
- Dual USB ports
- Dual firmware images
- Opus codec support
- T4U Auto-P template unified
- T4U firmware unified
- Up to 12 SIP accounts
- PoE support
- Dual-port Gigabit Ethernet
- USB headset and EHS support
- Wi-Fi via WF40/WF50
- Bluetooth via BT40/BT41
- Stand with 2 adjustable angles
- Wall mountable

# Yealink

#### Audio Features

- > HD voice: HD handset, HD speaker
- > Hearing aid compatible (HAC) handset
- > Acoustic Shield
- > Smart Noise Filtering
- > Wideband codec: AMR-WB (optional), Opus, G.722
- Narrowband codec: AMR-NB (optional), Opus, PCMU (G.711A), PCMA (G.711µ), G.723.1, G.729, G.729A, G.729B, G.729AB, G.726, iLBC
- > DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- > Full-duplex hands-free speakerphone with AEC
- > VAD, CNG, AEC, PLC, AJB, AGC

#### Phone Features

- > 12 VoIP accounts
- > One-touch speed dial, redial
- > Call forward, call waiting, call transfer, call hold
- > Call return, group listening
- > Emergency call
- > Mute, DND
- > Auto answer
  > Hoteline
- > 5-way conference call> Direct IP call without SIP proxy
- > Ring tone selection/import/delete
- Set date time manually or automatically
- > Dial Plan
- > XML Browser, Action URL/URI
- > RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- > Dual USB ports (2.0 compliant)
- Bluetooth earphone through BT40/BT41
- Contact synchronization through BT40/BT41
- Simultaneous connection of one headset and one mobile phone through BT40/BT41
- Wi-Fi through WF40/WF50
- USB call recording through USB flash drive
- USB headset
- Wireless Headset Adapter EHS40
- > USB/Bluetooth connectivity to Yealink CP900/CP700 speakerphone, USB connectivity to Yealink UH36 headset:
  - Basic functions: Answer / end, call mute
- Enhanced function: audio optimization, redial, call
- hold, volume synchronization, multiple calls control
- > Enhanced DSS key

#### Directory

- > Local phonebook up to 1000 entries
- > Black list

Learn More

- > XML/LDAP remote phonebook
- > Smart dialing
- > Phonebook search/import/export
- > Call history: dialed/received/missed/forwarded

YEALINK NETWORK TECHNOLOGY CO., LTD.

To find out how Yealink solutions can help your organization, visit us at www.yealink.com or mail to sales@yealink.com

#### **IP-PBX** Features

- > Busy Lamp Field (BLF), Bridged Line Apperance (BLA)
- > Anonymous call, anonymous call rejection
- > Hot-desking, voice mail
- > Flexible seating, Executive and Assistant
- > Call park, call pickup
- > Centralized call recording
- > Visual voice mail
- > Call recording

#### Display and Indicator

- >~2.7" 192x64-pixel graphical LCD with backlight
- > LED for call and message waiting indication
- > Dual-color (red or green) illuminated LEDs for line status information
- > Intuitive user interface with icons and soft keys
- > Multilingual user interface
- > Caller ID with name and number
- > Power saving

#### Feature keys

- > 6 line keys with LED
- > 6 line keys can be programmed up to 15 paperless DSS keys (3-page view)
- > 5 features keys: message, headset, mute, redial, hands-free speakerphone
- > 4 context-sensitive "soft" keys
- > 6 navigation keys
- > 2 volume control keys
- > Illuminated mute key
- > Illuminated headset key
- > Illuminated hands-free speakerphone key

#### Interface

- > 2 x RJ45 10/100/1000M Ethernet ports
- > Power over Ethernet (IEEE 802.3af), Class 2
- > 2 x USB port (2.0 compliant)
- > 1 x RJ9 (4P4C) handset port
- > 1 x RJ9 (4P4C) headset port

#### Other Physical Features

- > Color: Classic Grey
- > Stand with 2 adjustable angles
- > Wall mountable
- > External Yealink AC adapter (optional): AC 100~240V input and DC 5V/1.2A output
- > USB output currency: 5V === 500mA
- > Power consumption (PSU): 0.9-2.2W
- > Power consumption (PoE): 1.3-2.9W
- > Dimension (W\*D\*H\*T): 212mm\*189mm\*175mm\*54mm
- > Operating humidity: 10~95%

ି

> Operating temperature: -10~50°C (+14~122°F)

[]00[]

Wi-Fi/Bluetoo USB Donale

Email: sales@yealink.com

# Specifications

#### Management

- > Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- > Auto-provision with PnP
- > Broadsoft device management
- > Zero-sp-touch TR-069
- > Phone lock for personal privacy protection

> Proxy mode and peer-to-peer SIP link mode

> Time and date synchronization using SNTP

> QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP

> AES encryption for configuration file (AES256)

> GARP (Generic Attribute Registration Protocol)

- Ethernet Cable (2m CAT5E UTP Cable)

> Reset to factory, reboot

Network and Security

> Package tracing export, system log

> SIP v1 (RFC2543), v2 (RFC3261)

> Call server redundancy supported

> NAT traversal: STUN mode

> IP assignment: static/DHCP

> UDP/TCP/DNS-SRV(RFC 3263)

> Transport Layer Security (TLS 1.3)

> OpenVPN, IEEE802.1X, L2TP VPN

> HTTPS certificate manager

> Digest authentication

> LLDP/CDP/DHCP VLAN

> HTTP/HTTPS web server

> SRTP for voice

> IPv6

> ICF

> WPA2/WPA3

> Secure boot

Package Features

- Stand

> Package content:

- Quick Start Guide

> Qty/CTN: 5 PCS

> N.W/CTN: 5.8 kg

> G.W/CTN: 6.3 kg

Compliance

- Yealink SIP-T42U IP phone

- Handset with handset cord

- Power Adapter (Optional)

- Wall Mount Bracket (Optional)

> Giftbox size: 246mm\*223mm\*120mm

> Carton Meas: 627mm\*256mm\*235mm

Web: www.yealink.com

CE FC 🖉 REACH ISO 9001 💩 🙆

👎 broadsoft 30X ⊆Genesys

metaswitch Asterisk®

ELIQ / C



#### **About Yealink**

Yealink (Stock Code: 300628) is a global brand that specializes in video conferencing, voice communications and collaboration solutions with best-in-class quality, innovative technology and user-friendly experience. As one of the best providers in more than 140 countries and regions, Yealink ranks No.1 in the global market share of SIP phone shipments (Global IP Desktop Phone Growth Excellence Leadership Award Report, Frost & Sullivan, 2019).

#### Copyright

#### Copyright © 2021 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

#### **Technical Support**

Visit Yealink WIKI (http://support.yealink.com/) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (https://ticket.yealink.com) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD. Web: www.yealink.com Addr: No.1 Ling-Xia North Road, High Tech Park, Huli District, Xiamen, Fujian, P.R.C Copyright©2021 Yealink Inc. All rights reserved.